



800-634-8981 info@ameri-shred.com

◊ Capable of Shredding 500 - 2000 Hard Drives Per Hour ◊

**AMS-750HD / AMS-1000HD
HARD DRIVE SHREDDERS**
Durable, Reliable & Mobile

Options:

- Frame or stand model
- Fork pockets
- UL/CSA labeling
- Powder coat color
- Hard drive counter
- Air particulate system
- Stainless steel combers
- Lighted viewing window
- Backlit laser burned logos
- Mobile truck installation
- 3/4" and 1" shred widths on 10 HP



Voltage	Any 3-Phase
Infeed	11" W x 2.5" H
Motor	7.5 or 10 HP TEFC
Shred Width	1-1/2", 1" or 3/4"
Frame Model	Discharge Conveyor
Stand Model	Infeed Conveyor
Frame Model	79" L x 60" W x 66" H
Stand Model	72" L x 48" W x 84" H

SPECIFICATIONS

Model Number	Shred Width	Horse Power	Standard Drives / Hour	Enterprise Drives / Hour	Weight
AMS-1000HD	1-1/2"	10 HP	2000	1000	3100 Lbs.
AMS-750HD	1-1/2"	7.5 HP	1800	900	2700 Lbs.
AMS-1000HD	1"	10 HP	1500	750	3100 Lbs.
AMS-1000HD	3/4"	10 HP	1000	500	3100 Lbs.

INFEEED CONVEYOR WOULD NOT BE DIVIDED. HD-SSD MODEL SHOWN.

AIR FILTRATION SYSTEMS

Optional on Hard Drive Shredders Series 2 & Series 3

The AMS air filtration system was designed to help reduce possible odors and/or contaminants from escaping into the atmosphere during hard drive destruction.

Standard Features:

- Inexpensive and disposable pre-filter protects the blower and HEPA filter
- The blower is housed in cast aluminum
- The blast gate serves as an air flow control valve



SPECIFICATION CHART

Motor	1 HP TEFC
Air Flow	400 CFM at 3" static water gauge pressure
Efficiency	99.97% on particles 0.3 micron and larger

Ameri-Shred's air filtration systems consist of six major components which include the inlet, pre-filter, blower, blast gate, HEPA filter and ductwork.

An air filtration system must be part of your original order. It cannot be retrofit at a later date.